PANNELLO CONGLOMERATO LIGNEO



Finitura superiore
– laminato antistatico
– PVC
– gomma
– linoleum
– moquette
– parquet
– gres
– marmi e pietre naturali
– graniti naturali e ricomposti
– acciaio
– autoposanti: PVC, moquette
Anima del pannello
– Conglomerato ligneo
Rivestimento inferiore
– foglio alluminio
– lastra di acciaio zincato
– vaschetta in acciaio zincato
– laminato plastico a richiesta
Bordo Perimetrale
– materiale plastico antiurto, disponibile in diversi colori: Avorio, Grigio, Antracite e Nero, abbinabile al colore della finiture superiore
Traverso di collegamento
– traverso in acciaio zincato a sezione aperta o chiusa
Colonnina regolabile
– elemento verticale in acciaio zincato, regolabile in altezza

Upper Finish
– antistatic laminate
–PVC
– rubber
– linoleum
– carpet
– parquet
– porcelain stoneware
– marble and natural stone
– natural and engineered granite
– steel
– loose-laid finishes: pvc, carpet
Panel core
– wood particleboard core
– bottom covering
– aluminium foil
– galvanized steel sheet
– galvanized steel tray
– plastic laminate on request
Perimeter Edge
– impact-resistant plastic edge, available in various colours: Ivory, Grey, Anthracite and Black, matching the colour of the upper finish.
Stringer
– galvanized steel stringer with open or closed section.
Adjustable Pedestal
– vertical galvanized steel element, adjustable in height.

• **Spessore**
Spessore da 28 a 38 mm.

• **Principali vantaggi**
Ridotto peso proprio del pannello.
Elevata lavorabilità e adattabilità in cantiere.
Posa in opera semplice e rapida.
Ottimizzazione dei costi di fornitura e posa.
Buone prestazioni meccaniche e funzionali.

• **Composizione dell'anima**
Conglomerato ligneo FSC® in classe E 0,5 (secondo la Norma EN 717-2) a bassissima emissione di formaldeide.
Alta densità (730 kg/m³), che ne definisce le prestazioni meccaniche.

• **Thickness**
Thickness from 28 to 38 mm.

• **Main Advantages**
Lightweight panel construction.
High workability and adaptability on site.
Quick and easy installation.
Optimized supply and installation costs.
Good mechanical and functional performance.

• **Core Composition**
FSC® certified wood particleboard core, Class E 0,5 (according to EN 717-2), with very low formaldehyde emissions.
High density (730 kg/m³), ensuring excellent mechanical performance.